

Product sheet



LEGRAND

Bulkhead light - IP44 - IK06 - oval 60 W- E27 - metal grid no tool - grey

REF. 060414 | EAN. 3245060604141

[> Visit e-catalogue](#)

Product characteristics

- IP 44/54/55 weatherproof bulkhead lights - For domestic, commercial areas and tough environments
- Oval - IP 44 / IK 06 - Polypropylene base - Glass diffuser - Galvanised steel or plastic - Protection wire grid - 3 side knockable entries, for 16, 20 mm - cable - 230 V - 50 Hz - Self - extinguishing : 850 °C - For compact fluorescent lamps - Porcelain lampholder - Screw terminals 12 W - E 27 - Grey - Metal grid - no tool required

Technical characteristics

Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	No
Suitable for surface mounting	Yes
Suitable for light line configuration	No
Suitable for workplace according to EN 12464-1	No
Lamp type	Incandescent lamp
With light source	No
Suitable for number of light sources	1
Lamp holder	E27
Housing material	Plastic
Housing colour	Grey
Material cover	Glass structured
Type of grid	None
Voltage type	AC

Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dim function	Yes
Light distributor	Diffuser lens/optic/panel
Light sharing	Asymmetric
Beam angle	Extreme wide beam <gt;/>80°
Light outlet	Direct
Degree of protection (IP)	IP44
Degree of impact strength (IK)	IK06
Protection class	II
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24	No
Rated ambient temperature according to IEC 62722-2-1	-10-40 °C

Nominal voltage	207-253 V
Nominal current	261-545 mA
Type of control gear	Not required
With control gear	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming DSI	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off	No
Dimming phase cut-on	No
Dimming programmable	No
Dimming RF	No

Suitable for emergency lighting	No
With movement sensor	No
With light sensor	No
Covering of the luminaire with thermally insulating material possible	No
With air slots	No
Suitable for lamp power	60-60 W
Max. system power	60 W
Rated luminous flux according to IEC 62722-2-1	710 lm
Colour of light	White
Colour temperature	2700-2700 K
Colour rendering index CRI	90-100
Width	126 mm
Height/depth	105 mm
Length	175 mm
Built-in length	175 mm
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Documentation

CATALOGUE PAGE & OTHERS

- [ex223001_0901.pdf](#) | PDF (0.09Mo)
- [ex223001_0902.pdf](#) | PDF (0.09Mo)

Agreements & Certificates

- [LGRP-00121-V01.01-EN.pdf](#) | PDF (0.57Mo)