

Product sheet



P 17 TEMPRA LEGRAND

Surface mounting socket P17 - IP44 - 200/250 V~ - 16 A - 2P+E

REF. 555154 | EAN. 3245065551549

No price to display

> [Visit e-catalogue](#)

Product characteristics

- P 17 Tempra Pro IP 44 - LV 16 and 32 A - sockets , plugs , mobile sockets , appliance inlets and interlocked switched sockets
Surface mounting sockets - Two possible angles (5° or 25°) 200/250 V~ - IP 44 16 A - 2P+E

CEE socket outlet 16 A	1x16A xp xxxV
CEE socket outlet 32 A	None
CEE socket outlet 63 A	None
CEE socket outlet 125 A	None
Number of socket outlets with protective contact CEE 7/3 (type F)	1
Protection	None
Earth leakage switch	None
Number of miniature circuit breakers (MCB)	0
Housing material	Plastic

Power supply/connection possibility	Other
Diameter cable entry	M25
Handling	Wall mounting
Degree of protection (IP)	IP44
Military model	No
Colour	Grey
Height	131 mm
Width	93 mm
Depth	125 mm

Documentation

TECHNICAL DOCUMENTATION

- F01811FR-02.pdf | PDF (3.67Mo)
- LE05815AA-01.pdf | PDF (2.53Mo)
- F01811EN-03.pdf | PDF (9.37Mo)

CAD & Design specs / BIM

- surface_no_interlocked_sockets_200_250V.rfa | RFA (1.31Mo)
- Prises_non_verrouillées_saillies_200_250V.rfa | RFA (1.31Mo)

CATALOGUE PAGE & OTHERS

- ex223001_0529.pdf | PDF (0.05Mo)
- ex223001_0530.pdf | PDF (0.05Mo)
- ex223001_0525.pdf | PDF (0.12Mo)
- ex223001_0531.pdf | PDF (0.06Mo)

Agreements & Certificates

- IMQ-CA02.05950 | (0.42Mo)
- CCC-CQC2016010203837679 | (3.47Mo)



555154.dwg | DWG (0.13Mo)



OC / CB-FR_710665 | (0.7Mo)



LGRP-2014-112-V1-EN.pdf | PDF (1.02Mo)