

# Product sheet



## VALENA LIFE LEGRAND

2P+E socket with shut. Valena Life - automatic terminals - German standard -16 A -250 V~ -white

REF. 753120 | EAN. 3414970509659

[> Visit e-catalogue](#)

## Product characteristics

- Valena™ Life - socket outlets with cover plate - Valena In'Matic mechanisms supplied with cover plates and support frames - To be equipped with plates - IP 2X protection - Supplied with mounted dust protection transparent shield - Flowpack packaging: robust protection to ensure optimum operation
- German standard socket outlets 16 A - 250 V~2P+E sockets with shutters - Automatic terminals - White

## Technical characteristics

Model	Socket outlet CEE 7/3 (type F)
Protective contact	Other
Number of active contacts (round)	1
Number of active contacts (flat)	0
With complementary luminous signal	No
Number of ports USB-A	0
Number of ports USB-C	0
Number of units	1
Number of socket outlets switchable	0
Number of phases	1
Imprint/indication	None
Connection type	Push-in clamp
With hinged lid	No
With enhanced contact protection	Yes
Label space/information surface	No

Surface protection	Untreated
Surface finishing	Glossy
Antimicrobial treatment	No
With loop through function	Yes
With on/off switch	No
Colour of switch operator	White
Rotated central insert	No
Nominal current	16 A
Nominal voltage	250 V
Frequency	50-60 Hz
Suitable for degree of protection (IP)	IP20
Degree of impact strength (IK)	IK04
Device width	74.7 mm
Device height	74.7 mm
Device depth	40 mm
Compatible with Apple HomeKit	No

Colour	White
RAL-number (similar)	9003
Metallic colour	No
Transparent	No
Lockable	No
Eject-mechanism	No
Insulated mounting	No
With function lighting	No
With orientation lighting	No
Over voltage protection	No
Fault current protection	No
With miniature fuse	No
Special power supply	No special power supply
Mounting method	Flush-mounted
Type of fastening	Mounting with claw and screw
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes

Compatible with Amazon Alexa	No
Compatible with Google Assistant	No
IFTTT support available	No
With Wi-Fi signal repeater	No
With built-in bluetooth speaker	No
For heavy conditions according to VDE	No
Built-in depth	29 mm
Operating / setting temperature	-5-35 °C
Storage temperature	-5-35 °C
Voltage type	AC
Power Delivery	No
Cable nature for connection	Rigid
Cable section	2.5-2.5 mm <sup>2</sup>
Cable support	Other
Assembly arrangement	Basic element with central cover plate
Connected object	No

## Documentation

### TECHNICAL DOCUMENTATION

- F01949FR-01.pdf | PDF (1.5Mo)
- F01949EN-01.pdf | PDF (1.5Mo)

### Agreements & Certificates

- LGRP-01207-V01.01-EN.pdf | PDF (0.66Mo)
- OC / CB-HU-001784 | (1.45Mo)
- VDE-40044570 | (0.62Mo)
- OC / CB-HU-001410 | (0.87Mo)
- OC / CB-HU-003511 | (0.46Mo)
- MEEI-UP 69248331 0001, 0002, 0003 | (1.05Mo)