

## DATENBLATT INFiLED AR7.8 MK2 Ultra

### SYSTEM AR7.8 MK2 Ultra Blackface Outdoor Touring LED System

Pixel Pitch:	7,8mm
LED Konfiguration:	3-IN-1 SMD 1818 high brightness - Full Black
IC Treiber:	MBI 5264C
Receiving Card:	NOVA A10S PRO - HDR
Pixel pro Quadratmeter:	16.384 Pixel
Pixel pro Cabinet:	64 x 64 (500 x 500 mm Cabinet) 64 x 128 (500 x 1000 mm Cabinet)
Helligkeit:	4.000 nits
Wiederholrate:	7.680 Hz
Grauskalierung:	16 bit
Betrachtungswinkel:	160° h / 130° v
IP Zertifizierung:	IP 65
Leistungsaufnahme:	max. 660 W je qm ø 240 W je qm
Steckverbinder Power:	Neutrik® powerCON TRUE1
Steckverbinder Data:	Neutrik® etherCON
Spannung:	AC 100 - 250V
Abmessungen:	500 x 500 mm / 500 x 1000 mm (B x H)
Gewicht:	11,8 kg (500 x 500 mm Cabinet mit Windbrace) 17,8 kg (500 x 1000 mm Cabinet mit Windbrace)
Cabinet Material:	Aluminium
Zertifizierungen:	CE, ETL, FCC, RoHS, REACH, WEEE, Fireproof
Montage:	facettierbarer Aufbau +/-10° +/- 7,5° +/-5° +/-2,5° 0°
Processing:	NOVA COEX System - NCP

### Flyware & Stacking

Hanging Brackets:	Single Hanging Stacking Bracket 500 mm Double Hanging Stacking Bracket 1000 mm
Windload Frame:	Windload Frame mit Statik
Ground Stacking:	Ground Stacking mit Statik

500 x 1000 mm  
Cabinet



500 x 500 mm  
Cabinet



△ facettierbar



Neutrik®  
powerCON TRUE1



facettierbarer Aufbau  
+/- 10° / 7,5° / 5° / 2,5° / 0°



Neutrik®  
etherCON



Windload Frame

